

Metallised matt
floor treatment

Protects and restores
the matt finish
of varnished wood floors
and plastic flooring



Slip resistant
(in accordance with
standards NF P 90
106 and P 90 203)



Specially designed
to maintained all matt-
finished, varnished
wood floors subject
to heavy traffic



Gives a matt finish
to over-glossy floors



Odourless



Non-yellowing



Protector Matt (Métamat®)



PRODUCT DESCRIPTION

- **Blanchon Protector Matt (Métamat®)**'s new formula is specially developed to protect varnished wood floors with a matt finish. It keeps floors looking as good as new, prolongs their life and gives lacklustre floors a new shine.
- On high-traffic wood floors with a matt finish, **Protector Matt (Métamat®)** is the key element in making maintenance easier and quicker.
- **Protector Matt (Métamat®)** is ideal for giving a matt finish to over-glossy varnished wood floors or plastic flooring.
- Slip resistant (in accordance with Labosport standards F P 90 106 and NF P 90 203, available on request) and silicone-free.
- Non-yellowing, **Protector Matt (Métamat®)** is compatible with all wood floor lacquers and most modern flooring.
It is recommended for varnished wood floors, laminate floors, varnished cork and plastic flooring (see Surface Preparation).
- **Protector Matt (Métamat®)** is a white liquid which becomes totally transparent when dry.

SURFACE PREPARATION

- * **Protector Matt (Métamat®)** can be applied over all types of silicone-free wood floor lacquers. Before applying to pre-varnished wood floors, test on an inconspicuous area on the suitably prepared floor. Do not use on tiles, stone or other hard floors.
- Before applying, the varnished floor must have dried and hardened for at least 10 days.
- It is essential to clean the surface before it is treated with a damp⁽¹⁾ cloth or mop: use 1 L of Blanchon Remover diluted in 10 L of water and then rinse with a damp cloth⁽¹⁾.
- Apply **Protector Matt (Métamat®)** to a clean, dry, grease-free surface.

Important: on pre-varnished wood floors which can be very hygroscopic (easily absorbs moisture ie. beech, etc.), always test on an inconspicuous area before fully applying.

⁽¹⁾ A wood floor should never get too wet. Use a damp mop or cloth, well wrung out, never a soaking wet one.

DIRECTIONS FOR USE

- **Protector Matt (Métamat®)** is used neat, applying one or two coats. Apply with a sponge mop, a micro-fibre mop, a dust mop (Faubert) or a floor cloth (damp, never soaking wet).
- Wait 1 hour between each coat to allow for thorough polymerisation.

Cleaning of tools

- Rinse thoroughly with water immediately after use.
- Protect the environment:
 - Wring the tools properly and wipe them dry immediately after use.
 - Wash them in a dish with a small amount of water. Leave the used water to evaporate.
 - The accumulated dry sediments can be disposed of with trash.
 - Tightly close the container after use.
 - Return the empty container for recycling.
 - Please contact the local authorities for information on the collection and disposal of wastes.
 - Do not pour liquid wastes into sewer systems.

Blanchon

Protector Matt (Métamat®)

DRYING TIMES

- Dust-free: 15 minutes.
- Before recoating: 1 hour under normal conditions.
- Normal use of the area: 1h30 to 2 hours.

COVERAGE

- Approximately 40 m² to 50 m² per litre per coat.

MAINTENANCE

- Use a vacuum cleaner, broom or lamb's wool cloth. Do not polish too often as this can give a satin finish.
- Use Blanchon Maintenance diluted in a ratio of 1 to 3 or 1 to 5 with water and apply using a damp mop, never a wet one.
- Do not use abrasives, detergents or any products which contain ammonia or silicone.
- **Protector Matt (Métamat®)** can be applied over itself: apply a thin coat from time to time (using a micro-fibre mop or a sponge mop) to give a perfect finish.

TECHNICAL DATA

USE	Protecting and refinishing matt-finished varnished wood floors and plastic flooring
RESIN TYPE	Water-based, metal-complex, aliphatic acrylic-urethane
AFNOR CLASSIFICATION	Family I, class 7b
DENSITY	1.018 (at 20°C, as per NF T 30020)
REGULATORY INFORMATION	Refer to the relevant Safety Data Sheet (also available on www.blanchon.com or www.quickfds.com)
pH	8.5
BEFORE RECOATING	1 hour
TABER ABRASION RESISTANCE	N/A
IMPACT RESISTANCE	N/A
SCRATCH RESISTANCE	6H pencil
RESISTANCE TO HOUSEHOLD DETERGENTS	Protector Matt (Métamat®) is sensitive to alkaline detergents. Use Blanchon Maintenance instead of alkaline cleaning products
SURFACE MOISTURE	N/A
STORAGE	Protect from frost (be careful of storing in vehicles)

The information provided in this Technical Data Sheet is given in good faith for information purposes only. In no case whatsoever can this information be considered as a guarantee given by us nor engage our responsibility when our products are used. Since we are constantly striving to improve our products, the information given here may be subject to modification without prior notice. This Technical Data Sheet cancels and supersedes all previous versions.

Technical Data Sheet issued on the 05.2015

28 rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX - FRANCE Tél. 04 72 89 06 00 - Fax 04
78 70 07 18
Export Lines: Tel: (0033) 472 89 06 09
Fax: (0033) 472 89 06 02

Blanchon

BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board,
with a registered capital of 4 258 258
390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com
Internet : www.blanchon.com