

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** 901 BLACK BITUMEN PAINT

**Product code:** 901 - ALL SIZES

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

**Tel:** 0044 113 240 3456

**Fax:** 0044 113 240 0024

**Email:** sds@everbuild.co.uk

**1.4. Emergency telephone number**

**Emergency tel:** 0044 113 240 3456 (office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Flam. Liq. 3: H226; Asp. Tox. 1: H304

**Classification under CHIP:** -: R10; Xi: R38; N: R51/53

**Most important adverse effects:** Flammable liquid and vapour. May be fatal if swallowed and enters airways.

**2.2. Label elements**

**Label elements under CLP:**

**Hazard statements:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS08: Health hazard



# SAFETY DATA SHEET

901 BLACK BITUMEN PAINT

Page: 2

**Precautionary statements:** P243: Take precautionary measures against static discharge.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.  
Rinse skin with water/shower.  
P370+378: In case of fire: Use carbon dioxide, dry powder or foam for extinction.  
P403+235: Store in a well-ventilated place. Keep cool.  
P501: Dispose of contents/container to hazardous waste disposal site.  
P233: Keep container tightly closed.  
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
P331: Do NOT induce vomiting.  
P405: Store locked up.  
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/VPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

STRAIGHT RUN Kerosine - Solvent Naphtha (Petroleum), Medium Aliph.

EINECS	CAS	CHIP Classification	CLP Classification	Percent
265-191-7	64742-88-7	-	Asp. Tox. 1: H304	30-50%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. If symptoms persist, consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Not applicable.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor. If vomiting occurs, keep head low so that vomit doesn't enter lungs.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** Absorption through the lungs can occur causing symptoms similar to those of ingestion.

[cont...]

# SAFETY DATA SHEET

901 BLACK BITUMEN PAINT

Page: 3

## 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Dry chemical powder. Carbon dioxide. Alcohol or polymer foam. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. If outside keep bystanders upwind and away from danger point.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

[cont...]

# SAFETY DATA SHEET

901 BLACK BITUMEN PAINT

Page: 4

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Black

**Odour:** Characteristic odour

**Evaporation rate:** Moderate

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Non-viscous

**Flash point°C:** 23 - 55

**Autoflammability°C:** 230

**Vapour pressure:** n.d

**pH:** n/a

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

# SAFETY DATA SHEET

901 BLACK BITUMEN PAINT

Page: 5

## 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Direct sunlight. Sources of ignition. Flames. Hot surfaces.

## 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Relevant effects for mixture:**

Effect	Route	Basis
Irritation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** Absorption through the lungs can occur causing symptoms similar to those of ingestion.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

## Section 13: Disposal considerations

[cont...]

# SAFETY DATA SHEET

901 BLACK BITUMEN PAINT

Page: 6

## 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company. Dispose of according to local or national legislation

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT RELATED MATERIAL (OXIDIZED ASPHALT; STRAIGHT RUN KEROSENE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. MIXTURE)

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** III

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** No

### 14.6. Special precautions for user

**Tunnel code:** D/E

**Transport category:** 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

R10: Flammable.

[cont...]

# SAFETY DATA SHEET

901 BLACK BITUMEN PAINT

Page: 7

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Legend to abbreviations:** PNEC = predicted no effect level  
DNEL = derived no effect level  
LD50 = median lethal dose  
LC50 = median lethal concentration  
EC50 = median effective concentration  
IC50 = median inhibitory concentration  
dw = dry weight  
bw = body weight  
cc = closed cup  
oc = open cup  
MUS = mouse  
GPG = guinea pig  
RBT = rabbit  
HAM = hamster  
HMN = human  
MAM = mammal  
PGN = pigeon  
IVN = intravenous  
SCU = subcutaneous  
SKN = skin  
DRM = dermal  
OCC = ocular/corneal  
PCP = physico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.