

TECHNICAL DATA SHEET REV. 2**EVER BUILD STICK 2 All Purpose Clear Adhesive – 30ml****DESCRIPTION AND USES**

STICK 2 ALL PURPOSE CLEAR ADHESIVE is a strong, clear, quick drying adhesive suitable for a variety of household repairs and hobby uses. Will stick ceramics, porcelain, pottery, wood, card, paper, most plastics*, leather, cork, linoleum, rubber, stone, glass, metals and dense fabrics to both themselves and each other.

APPLICATION

Always open and use this product over a protected work surface.

Surfaces to be bonded must be clean, dry and free from dust. Use only in well ventilated areas. Do not breathe vapour. **POROUS SURFACES** (fabrics, ceramics etc) Unscrew cap and spread a thin even layer of adhesive onto **one** surface. Press two surfaces together firmly.

NON POROUS SURFACES (plastics, metals etc) Improve adhesion by abrading both surfaces with sandpaper.

Unscrew cap and spread a thin even layer of adhesive onto **both** surfaces. Allow adhesive to dry to a tough tacky finish (about 5-10 mins) then press both surfaces together firmly.

In both cases, full strength is obtained after 24 hours @20°C.

Replace cap immediately after use to keep adhesive usable.

STORAGE: Store in cool, dry conditions away from sources of ignition. Shelf life: 3 years from Date of manufacture in original unopened tubes.

CLEANING: Clean tools etc with acetone or nail varnish remover, protecting surrounding surfaces.

HEALTH AND SAFETY

EVERBUILD STICK 2 ALL PURPOSE CLEAR ADHESIVE Contains Acetone Proper shipping name: adhesive UN1133		
	HIGHLY FLAMMABLE	Highly flammable. Irritating to eyes Repeated exposure may cause skin dryness and cracking Vapours may cause drowsiness or dizziness. Keep out of reach of children Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition – NO SMOKING.
	IRRITANT	On case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately, and show this container/label Use only in well ventilated areas.
		Everbuild Building Products Ltd Site 41, Knowsthorpe Way, Cross Green Industrial Estate Leeds LS9 0SW. Tel. 0113 240 3456. Fax. 0113 240 0024

LIMITATIONS

*will not stick polyethylene, polypropylene, or PTFE.

Not suitable for bonding acetate, rayon or items which hold hot liquids.

Do not use near polished or some painted surfaces.

Do not use in areas subject to continuous water immersion.

Do not use on bitumen, asphalt or cellulose painted surfaces.

Do not use as a mirror adhesive as the product may attack the mirror backing.

Do not use below 5°C.

As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application.

Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that

The information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with

The stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information

Provided verbally by telephone to any prospective or existing customer.